# PIN(RCA) JACK

**S C P** □ □ □ — □ — □ — □ — □ — L R — □ □ □ — **G**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

① Series No.: SCP669(2P) ;
② Housing & Insulator color code:
"1" :Black ; "2" : Red ; "3" :White ; "4" : Yellow ; "5" : Blue ; "6" :Gray "
③ Schematic code: "A"; "B"; "C"; "D"; "E"
④ Bushing plating: "N" : Nickel (Standard) ; "G" : Gold flash
⑤ Terminal plating: "T" : Tin ; "S" : Sliver (Standard) ; "G" ; Gold flash
⑥ Insulator color code: Color code arrangement : L→R
"1" :Black ; "2" : Red ; "3" :White ; "4" : Yellow ; "5" : Blue ; "6" :Gray " 7" : Green " 8" : Orange "9" : Brown
⑦ Special option: "00C" : With cover
⑧ "G" : For RoHS compliant
** SCP805 Part No. is according to drawing

**S C P** □ □ □ — □ — □ — □ — T1 D1 T2 D2 T3 D3 — **G**

① ② ③ ④ ⑤ ⑥

① Series No.: SCP663/664/665/671/675/681/682/683/684/685/686/687/688/691/692/695/696/697/698
② Housing & Insulator color code:
"1" :Black ; "2" : Red ; "3" :White ; "4" : Yellow ; "5" : Blue ; "6" :Gray
③ Bushing plating: "N" : Nickel (Standard) ; "G" : Gold flash
④ Terminal plating: "T" : Tin ; "S" : Sliver (Standard) ; "G" ; Gold flash
⑤ Insulator color code: Color code arrangement : T1→D1→T2→D2→T3→D3(or L→R(2P)/ L→ C→ R(3P))
"1" :Black ; "2" : Red ; "3" :White ; "4" : Yellow ; "5" : Blue ; "6" :Gray " 7" : Green " 8" : Orange "9" : Brown
(P.S. 3P= XXXN00 ; XXXN03 for SCP675; XX0X00 for SCP671;
4P= XXXXT1 ; XXXXT2 for SCP687/688 only; 5P= XXXX0X for SCP671only)
** The customer special designed insulator color code arrangement is according to approve drawing
⑥ "G" : For RoHS compliant
** SCP672(4P) & (6P) Part No. is according to drawing

**S C P** □ □ □ — □ — □ — □ — T C D — □ — □ □ — **G**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

① Series No.: SCP643/644/645/655/660/661/662/666/667/668/678
② Position no.: "B": 2P ; "C" : 3P ; "F" : 6P (SCP655 only)
③ Bushing plating: "N" : Nickel (Standard) ; "G" : Gold flash
④ Terminal plating: "T" : Tin ; "S" : Sliver (Standard) ; "G" ; Gold flash
⑤ Insulator color code: Color code arrangement :
T→C→D ( L→R or L→C→R for SCP661/662/666/667 only)
"1" :Black ; "2" : Red ; "3" :White ; "4" : Yellow ; "5" : Blue ; "6" :Gray " 7" : Green " 8" : Orange "9" : Brown
** The customer special designed insulator color code arrangement is according to approve drawing
⑥ Schematic code: U; V ("0" for SCP643/644/645/655 only)
⑦ Special option: "00" : No special option
⑧ "G" : For RoHS compliant