






NUT



9.	Break Terminal	0.4T Brass	1	Silver Plated
8.	NUT	Low lead Brass Rod	1	Nickel plated
7.	Spring	SUS-304	1	
6.	Cover	PC	1	Trans Parent
5.	Housing	POM	1	Black Color
4.	Barrel(W/Thread)	Low lead Brass Rod	1	Nickel plated
3.	Tip Spring	0.25T Phosphor Bronze	1	Silver Plated
2.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
1.	Earth Terminal	0.4T Brass	1	Silver Plated
NO.	Description	Material	Q'TY	Finish



Pin Hole Layout
(Jack Bottom View)



S.C.PRECISION INDUSTRIAL CO., LTD.

DATE	DWN	CHKD	APVD	MANAGER
09.11.2020	王平華			

PART NAME: 3.5∅ PHONE JACK	PART NUMBER: SCJ354M1NWS1B00L	VERSION:1.0
TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT:mm	SCALE:1/1

SPECIFICATIONS:
Contact Resistance : 30mΩ max
Insulation Resistance : 100MΩ min. at DC 500V
Dielectric Withstanding Voltage: AC 500V for one minute
Remark: ▲: The Most Important Dimension

For Redference
僅供參攷

RoHS&SVHC
Compliant