



Pin Hole Layout  
(Jack Bottom View)

10.	Barrel	Low Lead Brass Rod	1	Nickel Plated
9.	Spring S	Piano Wire	1	
8.	Spring L	Piano Wire	1	
7.	Tip Spring	0.25T Brass	1	Silver Plated
6.	Shunt Terminal	0.3T Brass	1	Silver Plated
5.	Shunt Terminal	0.3T Brass	1	Silver Plated
4.	Ring Spring	0.25T Brass	1	Silver Plated
3.	Earth Terminal	0.3T Brass	1	Silver Plated
2.	Cover	PBT+15%	1	Black Color
1.	Housing	PBT+15%	1	Black Color
NO.	Description	Material	Q'TY	Finish

<b>S.C. PRECISION INDUSTRIAL CO., LTD.</b> 旭 全	DATE	DWN	CHKD	APVD	MANAGER
	07.12.2021	王平華			

PART NAME: 3.5 $\phi$ PHONE JACK	PART NUMBER: SCJ368R1NUS0B00L	VERSION: 2.0
----------------------------------	-------------------------------	--------------

TOLERANCE: $\pm 0.3$ mm UNLESS OTHERWISE SPECIFIED	UNIT: mm		SCALE: 1/1
--	----------	--	------------

**SPECIFICATIONS:**  
 Contact Resistance :30m $\Omega$  max  
 Insulation Resistance :100M $\Omega$  min.at DC500V  
 Dielectric Withstand Voltage: AC 500V for one minute  
 Remark:  $\blacktriangle$ : The Most Important Dimension

For Reference  
 僅供參考  
 RoHS&SVHC  
 Compliant