


NO.	Description	Material	Q'TY	Finish
12.	Washer	0.5T Steel	1	Nickel Plated
11.	Nut	2.0T Steel	1	Nickel Plated
10.	Insulator	POM	1	Ivory Color
9.	Insulator	Red Vulcanited Fibre	1	Red Color
8.	Barrel(W/Thread)	Low Lead Brass Rod	1	Nickel Plated
7.	Cover	0.5T Steel	1	Nickel Plated
6.	Housing	POM	1	Black Color
5.	Ring Spring	0.35T Phosphor Bronze	1	Silver Plated
4.	Transfer Terminal	0.4T Brass	1	Silver Plated
3.	Break Terminal	0.35T Phosphor Bronze	1	Silver Plated
2.	Make Terminal	0.2T Phosphor Bronze	1	Silver Plated
1.	Tip Spring	0.35T Phosphor Bronze	1	Silver Plated




S.C. PRECISION INDUSTRIAL CO., LTD.

DATE	DWN	CHKD	APVD	MANAGER
08.13.2021	王平華			

For Reference
僅供參考

RoHS&SVHC
Compliant

PART NAME : 6.3φ PHONE JACK

PART NUMBER: SCJ610M2NFS3B21L

VERSION: 1.0

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT: mm



SCALE: 1/1

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension