


Pin Hole Layout
(Jack Bottom View)

| | | | | |
|-----|----------------|----------------------|------|---------------|
| 6. | Washer | 0.5T Steel | 1 | Nickel Plated |
| 5. | Nut | 2.0T Steel | 1 | Nickel Plated |
| 4. | Cover | POM | 1 | Black Color |
| 3. | Housing | PBT | 1 | Black Color |
| 2. | Tip Spring | 0.3T Phosphor Bronze | 1 | Silver Plated |
| 1. | Earth Terminal | 0.3T Phosphor Bronze | 1 | Silver Plated |
| NO. | Description | Material | Q'TY | Finish |

| | | | | | |
|--|------------|-----|------|------|---------|
|  S.C. PRECISION INDUSTRIAL CO., LTD. 旭全 | DATE | DWN | CHKD | APVD | MANAGER |
| | 03.25.2022 | 王平華 | | | |

For Redference
僅供參考

RoHS&SVHC
Compliant

| | | |
|-----------------------------|-------------------------------|--------------|
| PART NAME : 6.3φ PHONE JACK | PART NUMBER: SCJ634P50HS1B00G | VERSION: 5.0 |
|-----------------------------|-------------------------------|--------------|

| | | |
|---|--|------------|
| TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED | UNIT: mm  | SCALE: 1/1 |
|---|--|------------|

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension