



Pin Hole Layout
(Jack Bottom View)

11.	Cover	POM	1	White Color
10.	Housing	PBT+15%	1	Black Color
9.	Make Terminal	0.20T Phosphor Bronze	1	Silver Plated
8.	Separator Spring	0.25T Phosphor Bronze	1	Silver Plated
7.	Break Terminal	0.30T Brass	1	Silver Plated
6.	Make Terminal	0.20T Phosphor Bronze	1	Silver Plated
5.	Separator Spring	0.25T Phosphor Bronze	1	Silver Plated
4.	Break Terminal	0.3T Brass	1	Silver Plated
3.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
2.	Tip Spring	0.3T Phosphor Bronze	1	Silver Plated
1.	Earth Spring	0.2T Phosphor Bronze	1	Silver Plated
NO.	Description	Material	Q'TY	Finish



S.C. PRECISION INDUSTRIAL CO., LTD.

DATE	DWN	CHKD	APVD	MANAGER
12.14.2021	王平華			

For Reference
僅供參考

RoHS&SVHC
Compliant

PART NAME : 3.5 ϕ PHONE JACK	PART NUMBER: SCJ348P00DS0B00G	VERSION: 4.0
TOLERANCE : ± 0.3 mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: 1/1

SPECIFICATIONS:
 Contact Resistance : 30m Ω max
 Insulation Resistance : 100M Ω min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: \blacktriangle : The Most Important Dimension