



Pin Hole Layout
(Jack Bottom View)

9.	Metal Shell	0.2T Phosphor Copper	1	Silver Plated
8.	Cover	PBT+15%	1	Black Color
7.	Housing	PBT	1	Black Color
6.	Tip Lead(TOP)	0.4T Brass	1	Silver Plated
5.	Tip Spring(TOP)	0.25T Phosphor Copper	1	Silver Plated
4.	Earth Terminal(TOP)	0.4T Phosphor Copper	1	Silver Plated
3.	Tip Spring(DOWN)	0.25T Phosphor Copper	1	Silver Plated
2.	Break Terminal(DOWN)	0.4T Brass	1	Silver Plated
1.	Earth Terminal(DOWN)	0.4T Phosphor Copper	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

S.C. PRECISION INDUSTRIAL CO., LTD. 旭全	DATE	DWN	CHKD	APVD	MANAGER
	06.03.2024	王放策			

PART NAME : 3.5φ PHONE JACK	PART NUMBER : SCJ351P00YS0BNSG	VERSION: 7.0
TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED		SCALE: 1/1

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲: The Most Important Dimension

For Redference
僅供參考

RoHS&SVHC
Compliant