



Pin Hole Layout  
(Jack Bottom View)

8.	Nut	Low Lead Brass Rod	1	Nickel Plated
7.	Barrel	Low Lead Brass Rod	1	Nickel Plated
6.	Spring L	Piano Wire	1	
5.	Tip Spring	0.25T Brass	1	Silver Plated
4.	Shunt Terminal	0.3T Brass	1	Silver Plated
3.	Earth Terminal	0.3T Brass	1	Silver Plated
2.	Cover	PBT+15%	1	Black Color
1.	Housing	PBT+15%	1	Black Color
NO.	Description	Material	Q'TY	Finish



**S.C. PRECISION INDUSTRIAL CO., LTD.**

DATE	DWN	CHKD	APVD	MANAGER
07.09.2021	王平華			

For Reference  
僅供參考

RoHS&SVHC  
Compliant

PART NAME : 3.5φ PHONE JACK	PART NUMBER: SCJ368M1NYS1B00L	VERSION: 2.0
-----------------------------	-------------------------------	--------------

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT: mm	SCALE: /
---	----------	----------

SPECIFICATIONS:  
 Contact Resistance : 30mΩ max  
 Current Rating : Max 0.5A , 12V DC  
 Insulation Resistance : 100MΩ min. at DC 500V  
 Dielectric Withstand Voltage : AC 500V for one minute  
 Remark: ▲: The Most Important Dimension